


PERMEABLE ROMAN



Lopez Color

Create beautiful, functional pavements while effectively managing storm water run-off using the Permeable Roman paver! The Permeable Roman pavers can be manufactured in any of the colors or textures shown on the Roman Paver colors page. (Note: the new Quad patterns do *not* apply to the Permeable Roman) Please call our Sales Office to check on color and texture availability. Our Permeable Roman pavers can also be integrated with our standard Roman Paver (see page 1) to provide selective areas of permeability.


Paver Sizes include the width of 1 spacer nub



Permeable Roman I



Permeable Roman II



Magnum Permeable Roman



Spacers protrude .29" (7.5 mm) from the main body

Void Area: minimum of 6.2% void
Thickness: 80 mm.

Packaging:
Permeable Roman I: 93 sq. ft. per pallet
Permeable Roman II: 94 sq. ft. per pallet
Permeable Magnum: 88 sq. ft. per pallet


Consult with a civil engineer to determine the base and sub-base requirements needed to achieve your project's objectives. Cast concrete, or pre-cast curbs are recommended for edge restraints when using an open-graded base. Reference ICPI Tech Spec 18 for more permeable pavement installation guidelines.




Brown Charcoal Color

Roman Patterns Using the Magnum


View additional patterns on our website



1-1-1
Pattern
27.2% I's
18.6% II's
54.2% Magnum's




2-2-2
Herringbone
Pattern
27.1% I's
18.7% II's
54.2% Magnum's




3-1-2
Herringbone
Pattern
39% I's
9% II's
52% Magnum's

Joint Patterns for Roman Permeable Pavers

View additional patterns on our website



Combo
Herringbone
60% Roman I
40% Roman II



I Pattern
75% Roman I
25% Roman II

TJP THIN JOINT PERMEABLE PAVER



Classic Grey Charcoal Blend

The Thin Joint Permeable (TJP) pavers create a 4.5 mm (3/16") joint. The smaller joints help keep the rock inside the joints as compared to some permeable pavers with larger joints, and will accommodate between 200" and 300" of precipitation per hour. The TJP pavers are manufactured only in an 80 mm thickness suitable for either commercial vehicular traffic or for residential applications. Use a No.9 to fill the joints with the TJP pavers.

Packaging:

TJP I: 93 sq. ft. per pal

TJP II: 94 sq. ft. per pal

TJP Rectangles: 92 q. ft. per pal

TJP Quad: 99 sq. ft. per pal


Air Vol Block stocks the TJP pavers in the Classic Bevel I and II shapes in our Sandstone Blend, Carmel Brown Blend, and Morro Bay Grey Blend. The Quad and Rectangle shapes, and the Euro-Cobble tumbled, or Pillow-Top textures can be special-ordered. Minimum order quantities and set-up charges may apply, so please contact our Sales Office for specifics.




Euro-Brown Charcoal Color

Shape: I


Classic Bevel Texture




II





Rectangle







Quad



Euro Cobble Texture



Pillow Top Texture




Carmel Brown



Sandstone Blend




Morro Bay Grey




Paso Robles Pattern

18% II's
12% I's
23% Rectangle
47% Quad



Buellton Pattern

19% II's
42% I's
39% Rectangle
0% Quad



Pismo Pattern

7% II's
0% I's
40% Rectangle
53% Quad

Additional installation patterns for the TJP pavers can be found at www.airvolblock.com. Consult with a civil engineer to determine the base and sub-base requirements needed to achieve your project's objectives. Cast concrete, or pre-cast curbs are recommended for edge restraints when using an open-graded base. Reference ICPI Tech Spec 18 for more permeable pavement installation guidelines.