

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name / Product code	: Amerimix Mortar Type M, S & N Portland Cement Lime Sand (AMX 400) Amerimix Mortar Type S Fast Set Portland Cement Cement Lime Sand (AMX 400-S FS) Amerimix Water Repellent Mortar Type N & S Portland Cement Lime Sand (AMX 410) Amerimix Pointing Mortar (AMX 420) Amerimix Stone Veneer Mortar - Buff (AMX 470) Amerimix Polymer Modified Stone Veneer Mortar (AMX 475/480/485) Amerimix Mortar Type M, S & N Masonry Cement & Sand (AMX 500) Amerimix Water Repellent Mortar Type M, N & S Masonry Cement & Sand (AMX 510) Amerimix Coarse Grout - Core Fill (AMX 600 CG) Amerimix Fine Grout - Core Fill (AMX 600 FG) Amerimix Self Consolidating Coarse Grout (AMX 610 CG) Amerimix Scratch Brown & Finish Stucco (AMX 700 SBF) Amerimix Water Mold Mildew Resistant Stucco (AMX 710 WMMR) Amerimix Premium Plus Stucco (AMX 715 Prem+ Stuc) Amerimix 2:1 Scratch Brown & Finish Stucco (AMX 760 2:1 SBF)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: Various.
------------------------------	------------

1.3. Details of the supplier of the safety data sheet

Oldcastle Architectural Inc.
900 Ashwood Parkway Suite 600
30338 Atlanta, GA - USA
T 800-334-0784 Tech Service: Monday - Friday; 8:00am - 5:00pm EST

1.4. Emergency telephone number

Emergency number	: CHEMTREC 1-800-434-9300 [USA] / +1 703-527-3887 [CAN]
------------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity 4 (Oral)
Skin Irritation 2
Serious Eye Damage 1
Skin Sensitization 1
Carcinogenicity 1A
Specific Target Organ Toxicity After Single Exposure 3
Specific Target Organ Toxicity After Repeated Exposure 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)	:	  
		GHS05 GHS07 GHS08

Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May cause respiratory irritation. Causes damage to lungs through prolonged or repeated exposure.
Precautionary statements (GHS-US)	: Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust. If exposed or concerned: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Rinse mouth. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center/doctor if you feel unwell. Store locked up. Store in a well ventilated place. Keep container tightly closed. Dispose of contents and container in accordance with all local, regional, national and international regulations.

AMX Series 400, 500, 600, 700

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

2.3. Other hazards

Other hazards not contributing to the classification : Not applicable.

2.4. Unknown acute toxicity (GHS-US)

Amerimix 2:1 Scratch Brown & Finish Stucco (AMX 760 2:1 SBF): 20% of the mixture consists of ingredient(s) of unknown acute toxicity.
Amerimix Polymer Modified Stone Veneer Mortar (AMX 475): 19% of the mixture consists of ingredient(s) of unknown acute toxicity.
Amerimix Stone Veneer Mortar - Buff (AMX 470): 18% of the mixture consists of ingredient(s) of unknown acute toxicity.
Amerimix Scratch Brown & Finish Stucco (AMX 700 SBF): 17% of the mixture consists of ingredient(s) of unknown acute toxicity.
Amerimix Water Mold Mildew Resistant Stucco (AMX 710 WMMR); Amerimix Premium Plus Stucco (AMX 715 Prem+Stuc); Amerimix Fine Grout - Core Fill (AMX 600 FG); Amerimix Water Repellent Mortar Type M, N & S Masonry Cement & Sand (AMX 510); Amerimix Mortar Type M, S & N Masonry Cement & Sand (AMX 500): 16% of the mixture consists of ingredient(s) of unknown acute toxicity.
Amerimix Water Repellent Mortar Type N & S Portland Cement Lime Sand (AMX 410): 14% of the mixture consists of ingredient(s) of unknown acute toxicity.
Amerimix Mortar Type M, S & N Portland Cement Lime Sand (AMX 400): 13% of the mixture consists of ingredient(s) of unknown acute toxicity.
Amerimix Coarse Grout - Core Fill (AMX 600 CG); Amerimix Self Consolidating Coarse Grout (AMX 610 CG); Amerimix Mortar Type S Fast Set Portland Cement Cement Lime Sand (AMX 400-S FS): 12% of the mixture consists of ingredient(s) of unknown acute toxicity.
Amerimix Pointing Mortar (AMX 420): 10% of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixture

Name	Product identifier	%
Quartz	(CAS No) 14808-60-7	60 - 100
Cement, portland, chemicals	(CAS No) 65997-15-1	10 - 35
Masonry cement	(CAS No) Proprietary mixture	10 - 30

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory tract irritation.

Symptoms/injuries after skin contact : Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitisation by skin contact.

Symptoms/injuries after eye contact : Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/injuries after ingestion : Harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Treat for surrounding material.

Unsuitable extinguishing media : Not available.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Advice for firefighters

Firefighting instructions : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

AMX Series 400, 500, 600, 700

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

6.2. Methods and material for containment and cleaning up

- For containment : Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Vacuum or sweep material and place in a disposal container.

6.3. Reference to other sections

No additional information available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin and eyes. Avoid generating and breathing dust. Do not swallow. Good housekeeping is important to prevent accumulation of dust. The use of compressed air for cleaning clothing, equipment, etc. is not recommended. Handle and open container with care. When using do not eat, drink or smoke.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Store in dust-tight, dry, labelled containers. Keep container tightly closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate matter)
OSHA	OSHA PEL (TWA) (mg/m ³)	50 µg/m ³
OSHA	Remark (OSHA)	Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m ³ / (%SiO ₂ +2)) for mg/m ³ . CAS No. source: eCFR Table Z-1.
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
Cement, portland, chemicals (65997-15-1)		
ACGIH	Local name	Portland cement
ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
ACGIH	Remark (ACGIH)	Pulm func; resp symptoms; asthma
ACGIH	Regulatory reference	ACGIH 2017
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
OSHA	OSHA PEL (TWA) (ppm)	50 mppcf
OSHA	Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
Masonry cement (Proprietary mixture)		
ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³

8.2. Exposure controls

- Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
- Hand protection : Wear suitable waterproof gloves.
- Eye protection : Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).
- Skin and body protection : Wear suitable waterproof protective clothing.
- Respiratory protection : A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

AMX Series 400, 500, 600, 700

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Other information : Handle according to established industrial hygiene and safety practices. Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid.
Appearance : Powder.
Colour : Various.
Odour : Characteristic.
Odour threshold : No data available.
pH : 12 - 13
Relative evaporation rate (butylacetate=1) : No data available.
Melting point : No data available.
Freezing point : No data available.
Boiling point : No data available.
Flash point : No data available.
Self ignition temperature : No data available.
Decomposition temperature : No data available.
Flammability (solid, gas) : Not Flammable.
Vapour pressure : No data available.
Relative vapour density at 20 °C : No data available.
Relative density : No data available.
Solubility : No data available.
Log Pow : No data available.
Log Kow : No data available.
Viscosity, kinematic : No data available.
Viscosity, dynamic : No data available.
Explosive properties : No data available.
Oxidising properties : No data available.
Explosive limits : No data available.

9.2. Other information

VOC content : 0%, Not applicable; 0 wt, Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Keep dry in storage.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Incompatible materials. Moisture.

10.5. Incompatible materials

Wet cement is alkaline and incompatible with acid, ammonium salts and aluminum metal.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed.

Quartz (14808-60-7)	
LD50 oral rat	500 mg/kg
AMX Series 400, 500, 600, 700	
ATE (oral)	530.2 mg/kg - 653.8 mg/kg, rat
ATE (dermal)	No data available.

AMX Series 400, 500, 600, 700

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

AMX Series 400, 500, 600, 700	
ATE (inhalation)	No data available.

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: May cause cancer.

Quartz (14808-60-7)	
IARC group	1
National Toxicity Program (NTP) Status	2

Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Causes damage to organs through prolonged or repeated exposure. (Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.)
Aspiration hazard	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitisation by skin contact.
Symptoms/injuries after eye contact	: Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: Harmful if swallowed. May cause stomach distress, nausea or vomiting.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.
-------------------	--

12.2. Persistence and degradability

AMX Series 400, 500, 600, 700	
Persistence and degradability	No data available.

12.3. Bioaccumulative potential

AMX Series 400, 500, 600, 700	
Bioaccumulative potential	No data available.

12.4. Mobility in soil

AMX Series 400, 500, 600, 700	
Ecology - soil	No data available.

12.5. Other adverse effects

Other adverse effects	: No data available.
-----------------------	----------------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: This material must be disposed of in accordance with all local, state, provincial, and federal regulations.
--------------------------------	---

SECTION 14: Transport information

In accordance with DOT:

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

AMX Series 400, 500, 600, 700

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

14.3. Additional information

Other information : No supplementary information available.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Gypsum (Ca(SO ₄).2H ₂ O)	CAS-No. 13397-24-5
---	--------------------

15.2. US State regulations

No additional information available

15.3. US State regulations

⚠ WARNING: This product can expose you to Quartz, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Date of issue : 03/06/2014


Revision date : 01/29/2019

Data sources : SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product